

## mighty-blade® FLANGED IMMERSION HEATERS

### CLEAN AND POTABLE WATER HEATING – 82 watts/sq. in.

4" 150 LB ASASTAINLESS STEEL FLANGE				CATALOG NUMBERS	
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 22	FIG. 23
30	240	2	16½	H4A-6-0255-M1	H4A-6-0255-M7
	480	1		H4A-6-0256-M1	H4A-6-0256-M7
40	240	2	19½	H4A-6-0257-M1	H4A-6-0257-M7
	480	2		H4A-6-0258-M1	H4A-6-0258-M7
50	480	2	24½	H4A-6-0259-M1	H4A-6-0259-M7
63	480	2	30	H4A-6-0260-M1	H4A-6-0260-M7
76	480	2	35	H4A-6-0261-M1	H4A-6-0261-M7

6" 150 LB ASASTAINLESS STEEL FLANGE				CATALOG NUMBERS		
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 24	FIG. 25	FIG. 26
75	240	5	16½	H6A-15-0456-M1	H6A-15-0456-M5	H6A-15-0456-M6
	480	5		H6A-15-0457-M1	H6A-15-0457-M5	H6A-15-0457-M6
100	240	5	19½	H6A-15-0458-M1	H6A-15-0458-M5	H6A-15-0458-M6
	480	5		H6A-15-0459-M1	H6A-15-0459-M5	H6A-15-0459-M6
125	480	5	24½	H6A-15-0460-M1	H6A-15-0460-M5	H6A-15-0460-M6
160	480	5	30	H6A-15-0461-M1	H6A-15-0461-M5	H6A-15-0461-M6
190	480	5	35	H6A-15-0462-M1	H6A-15-0462-M5	H6A-15-0462-M6

### PROCESS WATER, SOLUTION WATER, 50% ETHYLENE GLYCOL HEATING – 40 watts/sq. in.

4" 150 LB ASA STAINLESS STEEL FLANGE				CATALOG NUMBERS	
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 22	FIG. 23
12	240	1	13¾	H4A-6-0243-M1	H4A-6-0243-M7
15	240	1	16	H4A-6-0244-M1	H4A-6-0244-M7
18	240	1	18¾	H4A-6-0245-M1	H4A-6-0245-M7
24	240	2	22¾	H4A-6-0246-M1	H4A-6-0246-M7
	480	1		H4A-6-0247-M1	H4A-6-0247-M7
30	240	2	27¾	H4A-6-0248-M1	H4A-6-0248-M7
	480	1		H4A-6-0249-M1	H4A-6-0249-M7
36	240	2	32¾	H4A-6-0250-M1	H4A-6-0250-M7
	480	1		H4A-6-0252-M1	H4A-6-0252-M7
48	480	2	42¾	H4A-6-0253-M1	H4A-6-0253-M7
60	480	2	51¾	H4A-6-0254-M1	H4A-6-0254-M7

6" 150 LB ASASTAINLESS STEEL FLANGE				CATALOG NUMBERS		
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 24	FIG. 25	FIG. 26
30	240	5	13¾	H6A-15-0445-M1	H6A-15-0445-M5	H6A-15-0445-M6
37.5	240	5	16	H6A-15-0446-M1	H6A-15-0446-M5	H6A-15-0446-M6
45	240	5	18¾	H6A-15-0447-M1	H6A-15-0447-M5	H6A-15-0447-M6
60	240	5	22¾	H6A-15-0448-M1	H6A-15-0448-M5	H6A-15-0448-M6
	480	5		H6A-15-0449-M1	H6A-15-0449-M5	H6A-15-0449-M6
75	240	5	27¾	H6A-15-0450-M1	H6A-15-0450-M5	H6A-15-0450-M6
	480	5		H6A-15-0451-M1	H6A-15-0451-M5	H6A-15-0451-M6
90	240	5	32¾	H6A-15-0452-M1	H6A-15-0452-M5	H6A-15-0452-M6
	480	5		H6A-15-0453-M1	H6A-15-0453-M5	H6A-15-0453-M6
120	480	5	42¾	H6A-15-0454-M1	H6A-15-0454-M5	H6A-15-0454-M6
150	480	5	51¾	H6A-15-0455-M1	H6A-15-0455-M5	H6A-15-0455-M6